



Entrance Armor Rib 37 Technical Data

Product Description

Material	100% Asota® solution dyed UV stabilized polypropylene fibers
Backing	EcoDi composite rubber
Roll Sizes	6'7"x approx. 68'8"; 13'2"x approx. 68'8"
Custom Sizes	Custom lengths up to 68'8"

Technical Data

	Test	Requirement	Dimensions
Pile Height	ISO 1776	Inches	9/32"
Total Height	ISO 1776	Inches	3/8"
Pile Height	ISO 8543	Ounces per square yard	37 oz/sq yd
Total Weight	ISO 8543	Ounces per square yard	65.5 oz/sq yd.

Safety

Surface Flammability	ASTM D2859 CPSC FF 1-70	Test specimen must be greater than 1" in at least 7 of 8 specimens tested	Passes
----------------------	----------------------------	---	--------

Color Fastness

To Light	ISO 105 B02	1 = considerable change; 6 = negligible or no change	6
To Water	ISO 105 E01	1 = considerable change; 6 = negligible or no change	5
To Rubbing	ISO 105-12	1 = considerable change; 6 = negligible or no change	4

LEED

MR Credit 4	LEED-NC v.3	For 1-2 points: \$ value of all materials min. average 10% recycled content	20 % post recycled (post-consumer)
IEQ Credit 4.1	LEED-NC v.3	For 1 point: low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet adhesive	Multi-Bond VOC: 0 g/L
IEQ Credit 4.3	LEED-NC v.3	For 1 point: low-emitting flooring per Green Label Plus or FloorScore™	Green Label Plus Certified
IEQ Credit 5	LEED-NC v.3	For 1 point: semi-permanently installed entrance system at least ten feet in length and maintained on a weekly basis by a contracted service organization	Entrance Armor Rib 37 is designed for semi-permanent installation